

SF-IPT943HA-2E

2 MP IP Camera
1/2.8" Progressive Scan CMOS
Compression H.265+, H.265, H.264+,
H.264
Built-in microphone
Lens 2.8 mm / IR LEDs Range 30 m
WEB, CMS Software, Smartphone
and NVR



Safire
IP camera
ECO Range
1/2.8" Progressive Scan CMOS
2 Megapixel (1920x1080)
2.8 mm Lens
0 Lux
IR Range 30 m
Compression H.265+/H.265/H.264+/H.264
Built-in microphone
RJ-45 10/100 BaseT
PoE IEEE802.3af
Weatherproof IP66
IR Cut
WEB, CMS, Smartphone and NVR interface
ONVIF Compatible

Specifications

Brand	SAFIRE
Image sensor	1/2.8" Progressive Scan CMOS
Maximum resolution	2 Megapixel (1920x1080)
Main Stream rate	30 fps (1920 × 1080, 1280 × 960, 1280x720)
Extra Stream rate	30 fps × (640 360,x 320 240)
Compression	H.265+, H.265, H.264+, H.264
Bitrate	32 Kbps – 8 Mbps
Lens	2.8 mm (H: 112.1°, V: 60.0°, D: 132.2°)
Minimum illumination	0.028 Lux (colour) / 0 Lux (B/N)
Infrared lighting	0 Lux / IR LEDs (30 m)
Image improvements	WDR, BLC, 3D-DNR, AWB, ROI, Motion detection, Mirror
Day / Night	Removable mechanical ICR filter
Audio	Integrated microphone
Alarm	No
Network interface	Ethernet 10/100 BaseT
Remote access	Web browser, Safire Control Center Smartphone App and PC Software
Interoperability	ONVIF, PSIA, CGI, ISAPI
Power	12 VDC / 400 mA, PoE IEEE802.3af
Internal memory	MicroSD card up to 256 GB
Degree of protection	Weatherproof IP66
Temp. operation	-30° C ~ +60° C
Dimensions	Ø110 mm × 85.3 mm
Weight	320 g