

SF-NVR6216-4K16P

NVR for IP cameras
16Ch video / 16 PoE Port(s)
Max Resolution 8.0 Mpx /
Compression H.265+
Bandwidth 160 Mbps
Outputs 4K HDMI & VGA
Space for 2 hard disks



Safire
NVR for IP cameras
16 CH
160 Mbps bandwidth supported
Maximum resolution 8 Megapixel
Compression H.265+/H.265/H.264+/H.264
Alarms
VGA and HDMI 4K output
IP Dual Stream Access
Mouse
Space for 2 HDD
16 PoE ports IEEE802.3af/at
WEB, CMS and Smartphone interface
ONVIF Compatible

Specifications

Brand	Safire
Inputs for IP cameras	LAN port up to 16 channels
Power over Ethernet	16 port PoE Switch IEEE802.3af/at (max. 200 W)
IP compatible cameras	SAFIRE (native protocol), ONVIF
Bidirectional audio	1 input / 1 RCA output
Video outputs	1 HDMI 4K, 1 VGA
Video compression format	H.265+ / H.265 / H.264+ / H.264
Display resolution	3840x2160, 2560x1440, 1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
Total bandwidth	160 Mbps downstream / 160 Mbps upstream
Main Stream recording	8MP/6MP/5MP/4MP/3MP/1080P /UXGA /720P /VGA /4CIF /DCIF /2CIF /CIF /QCIF
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Alarms	4 Inputs / 1 Relay NO/NC
Recording method	Manual, programmed, motion detection
External Backup	USB memory / HDD USB / CD-RW USB / DVR-RW USB
Internal memory	2 SATA HDD 3.5" of up to 6 TB (not included)
Communication	1 x USB 3.0 / 1 x USB 2.0 / 1 x RJ45 (Ethernet)
Remote access	Web browser, Safire Control Center Smartphone App and PC Software
Power	AC 100~240 V, 50/60 Hz
Dimensions / Weight	52 (H) x 385 (W) x 315 (D) mm / 3 Kg