

SF-IPB026WA-4P-HV

4 MP IP Camera
1/3" Progressive Scan CMOS sensor
Motion Detection 2.0 of humans and vehicles
2.8 mm lens / WDR / IR 40m
Compression H.265+ / H.265
Built-in microphone / POE



Safire
IP Camera PRO range
1/3" Progressive Scan CMOS Ultra Low Light
4 Megapixel (2592x1944)
2.8 mm Lens
WDR
Compression H.265+/H.264+
IR Cut
0 Lux
IR Range 40 m
Motion Detection 2.0: Human and vehicle motion detection
Integrated microphone
RJ-45 10/100 BaseT
WEB, CMS, Smartphone and NVR interface
ONVIF Compatible
PoE IEEE802.3af
Weatherproof IP67

Specifications

Brand	SAFIRE
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2688x1520)
Minimum illumination	0.005 Lux / F1.6 Colour
Infrared lighting	0 Lux / IR LEDs (40 m)
Lens	2.8 mm (H:103°, V: 55°)
Bitrate	32 Kbps – 8 Mbps
Main Stream rate	4Mpx / 3Mpx / 1080p / 720p (1 – 25 FPS)
Extra Stream rate	640x480, 640x360, 320x240 (1 ~ 25 FPS)
Compression	H.265+ / H265 / H.264+ / H264
Image improvements	WDR (120dB), BLC, 3D-DNR, MD, ROI
Motion Detection 2.0	Advanced motion detection of humans and vehicles on the scene
Advanced features	Line-crossing detection intrusion entry / exit area
Day / Night	Removable mechanical ICR filter
Internal memory	MicroSD card, Max 256 GB
Network interface	Ethernet 10/100 BaseT
Alarms	No
Audio	Built-in microphone
Remote access	NVR, Web Browser, App Smartphone and PC Software Safire Control Center
Interoperability	ONVIF
Power	DC 12V / 0.5A, max. 6W, PoE IEEE802.3af max. 7W
Degree of protection	IP67
Material	Metallic
Temp. operation	-30° C ~ +60° C
Dimensions	161.7 mm (H) x 70 (Ø) mm
Base dimensions	55 (Ø) mm (3 screws)
Weight	490 g