

# SF-VIMOD-CAM-2

2- wires Safire Video Intercom

Camera 2Mpx

Bidirectional audio

Mobile APP via Monitor

Suitable for exterior IP65

Modular



Safire - second generation

2 wire video-intercom with 2Mpx camera

Adjustable wide angle lens

Integrated speaker and microphone

IR night vision

TCP/IP connection via SF-VIMOD-HUB

Remote monitoring through Safire Control Center-software, mobile app or interior monitor

Remote door opening

Surface mount or flush mount with bracket not included

Retro-illuminated name tag

Suitable for exterior IP65

Can be integrated with Safire modules

# Specifications

|                             |  |
|-----------------------------|--|
| <b>Brand</b>                | Safire   |
| <b>Operating system</b>     | LINUX OS   |
| <b>Image sensor</b>         | Low Illumination 2 MP IR                                   |
| <b>Image Functions</b>      | BLC / WDR / DNR  |
| <b>Viewing angle</b>        | D: 180° H:96°  |
| <b>Audio</b>                | Bidirectional audio with microphone and speaker            |
| <b>Keypad</b>               | Mechanical button with LED backlit name-tag                |
| <b>Outputs</b>              | 2 relay / 1 module output / External power supply required |
| <b>Inputs</b>               | 4 inputs   |
| <b>Remote access</b>        | Mobile app or Safire Control Center-software               |
| <b>Network interface</b>    | Two-Wire Networking / SIP Protocol 2.0                     |
| <b>Modular</b>              | Compatible with Safire extension modules                   |
| <b>Power</b>                | DC 24 VDC with Hub 2 wires / 12 V / 1700 mA max.           |
| <b>Degree of protection</b> | IP65   |
| <b>Material</b>             | Stainless steel  |
| <b>Temp. operation</b>      | -40° C ~ +60° C  |
| <b>Dimensions</b>           | 98 (H) x 99.8 (W) x 43.9 (D) mm                            |
| <b>Weight</b>               | 360 g  |