

# SF-IPSD8732ITA-4US-PAN

4 MP Ultra Low Light Motorised IP  
Camera  
1/2.8" Progressive Scan CMOS  
Compression H.265+/ H.265 /  
H.264+/ H.264  
5.9~188 mm Lens (32X) Auto Iris  
IR LEDs Range 200 m  
Truesense: Human and vehicle false  
alarm filter



Safire  
IP camera  
1/2.8" Progressive Scan CMOS Ultra Low Light  
4 Megapixel (2560x1440)  
5.9~188.8 mm Lens  
Optical Zoom X32  
WDR  
Compression H.265+/H.264+  
IR Cut  
0 Lux  
IR Range 150 m  
TrueSense, false alarm filter for vehicles and people  
Face Capture: Compatible with facial recognition recorders  
RJ-45 10/100 BaseT  
Autotracking  
WEB, CMS, Smartphone and NVR interface  
ONVIF Compatible  
Micro SD card recording  
PoE IEEE802.3af  
Weatherproof IP66  
Vandal proof IK10

# Specifications

Brand	Safire
Image sensor	1/2.8" Progressive Scan CMOS
Resolution	4 Megapixel (2560x1440)
Minimum illumination	PTZ: 0.0005 Lux (F1.5) / B/W: 0.001 Lux (F1.5) Panoramic: 0.0005 Lux (F1.6) / GO: 0 Lux
Compression	H.265+ / H.265 / H.264+ / H.264
Lens	Varifocal 5.9-188 mm (Optical Zoom 32X)
Digital zoom	16X
Electronic shutter	1/1s-1/30000s
Day / Night	Removable mechanical ICR filter
Image improvements	BLC, HLC, WDR, 3D-NR, AGC, AWB, MD, Privacy Masking, ROI
Video analysis	VCA: Tripwire   Area intrusion   Audio exception
Advanced functions	TrueSense with false alarm filtering for vehicles and people   Line Crossing   Intrusion
Face Capture	Up to 5 captures at a time, compatible with facial recognition recorders
Pan/Tilt Range	Horizontal: 360°, Vertical: -15°-90° auto flip
Manual speed	Horizontal: 0.1° ~ 160°/sec, Vertical: 0.1° ~120°/s
Speed between Presets	Horizontal: 240° /s, Vertical: 200° /s
Preset positions	300 preset, 4 auto pattern, 8 auto tour, auto pan, auto scan
Internal memory	MicroSD card, Max 256 GB
Audio	1 input / 1 output
Alarms	2 input / 1 output
PTZ Control	Through network access
Network interface	Ethernet 10 / 100 BaseT
Remote access	Web browser, Safire Control Center Smartphone App and PC Software
Interoperability	ONVIF, PSIA, CGI
Power	24 VAC Hi-PoE / 42W (max)
Temp. operation	-30° C ~ +65° C
Degree of protection	IP66 / IK10 / Overvoltage 6000V
Dimensions (without bracket)	382.1 mm (H) x 220 (Ø) mm
Weight (without bracket)	4.5 kg